

H15P SIP Horn Speaker - 15W

The H15P SIP Horn speaker is ideal for outdoor applications. It can work as standalone or integrate with IP Phone Systems enabling users to make announcements from IP Phones. H15P supports 2 SIP accounts, one account can also be used as a loud ringer/ alerter in noisy environments to notify users of phones ringing.



- SIP Enabled with Opus, G722 HD sound
- Integrates with IP PBX systems
- Supports P2P Paging and RTP Multicast
- Built in D class stereo 15W amplifier
- Supports scheduling of prerecorded messages
- Can be used as loud ringer
- Programming by web login
- IP67 Water proof enclosure
- PoE for easy installation
- 30W option available

Specifications

Audio Decoding	OPUS 48kHz, G722 16 kHz, PCMU / PCMA 8 kHz, MP3 44.1 kHz.
Network Protocols	TCP/IP, UDP, ARP, ICMP, SIP, RTSP, NTP, DHCP, HTTP, RTP, RTCP, FTP, TFTP, ONVIF
Speaker Acoustics	SPL 113dB, Signal to noise ratio 91dB, Harmonic Distortion 0.1@1kHz
Speaker Frequency	Response 300Hz~8kHz, Range 500-2kHz +/-10dB, 400-12kHz +/-20dB.
Operating temperature	-30°C~+60°C, Operating humidity 5%~85%.
Dimensions & Weight	ABS IP67 rated enclosure 225 x 165 x 240mm, 1.30 Kg.
Network and Power	RJ45 socket with IEEE802.3af compliant PoE .