

# G15P - SIP Paging Adapter & Scheduler

The G15P SIP Paging Adapter & Scheduler is an ideal solution for connecting legacy analog speakers or amplifiers to an IP or SIP PA System. The various interface options combined with web-based setup and PoE makes it easy to quickly configure a PA solution.



- HD Opus Codec ensures excellent Sound
- 2 x SIP Accounts with option to use as ringer
- Supports G722, G711 PCMU & PCMA, MP3 Codecs
- Scheduler for playing audio files or bell tones
- Headset output with 32 Ohm impedance for amplifier
- Built in 15W amplifier with speaker interface
- Supports SIP Direct Call and RTP Multicast
- 10/100 Network interface with PoE for easy installation
- Web interface for easy setup and management
- Volume Control keys to adjust output volume

## G15P - SIP Paging Adapter & Scheduler Specification:



### Audio

Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
-------	--

### Network

Security	Password protection, IP address filtering, Digest authentication, User access log, Firewall
----------	--

Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
------------------	--

Network Interface	10/100 Base-TX, RJ45
-------------------	----------------------

VoIP	Supports SIP protocol for integration with IP Phone systems Option to use SIP account as Ringer with various ring tones 2 * SIP Accounts, SIP Direct IP Call, RTP Multicast Codecs: OPUS, MP3, G.722, PCMU, PCMA
------	---

### Amplifier

Amplifier description	Built-in 15W Amplifier
-----------------------	------------------------

### General

Material	Metal
----------	-------

Power Supply	PoE or DC 12V/24V
--------------	-------------------

Interface	1* MIC input, 1* Headset output, 1* Speaker output, 2* GPIO Alarm input, 1* GPIO Alarm output, 2* Relay Alarm output
-----------	--

Dimensions & Weight	112mm *105mm * 29mm, 250gm.
---------------------	-----------------------------